

Other

The following features or practices are recommended. They will become required features when the 2010 California Building Code becomes effective.

3. **Formaldehyde Limits**: Formaldehyde limits for wood products shall meet Table 804.4.4 of the California Green Building Code.
4. **Water Budget for Landscaping**: Where landscape irrigation is proposed, a water budget shall be developed that conforms to the California Department of Water Resources Model Water Efficient Landscape Ordinance, or other applicable local regulations.
5. **Provide Recycling Area**: Provide a readily accessible area for depositing, storage and collection of recyclable items (as applicable).
6. **Seal Duct Openings**: Cover and seal duct openings during construction for all new and existing ductwork in proximity of the construction.
7. **VOC Limits**: Use only interior paints/wood finishes and adhesives that contain low, or no volatile organic compounds (VOCs).
8. **Install Low-Flow Plumbing Fixtures**: New plumbing fixtures shall have a net saving of 20 percent over minimum requirements. Multiple showerheads serving one shower shall have a total water usage no greater than 2gpm @ 80psi.
9. **Construction & Demolition Waste Reduction**: Provide documentation (e.g. landfill or donation receipts) demonstrating that 100% of recyclable/reusable construction/demolition waste has been recycled, salvaged or donated.
10. **Provide Operation and Maintenance Binder/Manual**: Provide an operation and maintenance binder/manual for all new appliances and systems installed as part of the scope of work.